

Productive  
and versatile.

imageRUNNER ADVANCE  
4025i, 4035i, 4045i, 4051i

you can

Efficient high quality output for busy workgroups and small departments, this smart multifunctional will enhance your document workflows and safeguard confidential information.

25 – 51  
PPM PPM  
MONO

INTUITIVE USER  
INTERFACE

MEAP  
PLATFORM

UP TO 4,980 SHEET  
PAPER CAPACITY

FLEXIBLE  
FINISHING  
OPTIONS

MODULAR DESIGN



### Productivity

- Customisable 8.4" (21.3 cm) colour touch-screen
- Colour duplex scanning and send capabilities
- Powerful integration and scanning into business applications
- Up to 4980 sheet paper capacity for busy workgroups
- Extensive internal and external finishing options
- Consistent operation and accessibility features.

### Cost Control

- Efficient black and white output for the whole workgroup
- User based reporting, restriction and redirection via uniFLOW
- Options for cost recovery and coin-vending integration
- Modular design and resource sharing capability
- Efficient monitoring and management capabilities.

### Device and information security

- A range of user-based authentication options
- Secure print, Mailbox and address filtering as standard
- Trusted Platform Module (TPM) encrypts login information
- Options to restrict access to functions by user i.e. Send
- A range of powerful security hardening options
- Integrates with uniFLOW Data Loss Prevention & auditing capabilities
- Supports industry standards and protocols for compliance.

### Environmental credentials

- Class leading energy efficiency – as low as 1 watt
- Low Typical Electricity Consumption (TEC)\* rating
- ENERGY STAR® qualified
- Incorporates recycled materials and Bio plastics.

 **imageRUNNER**  
ADVANCE

**Canon**

# Specifications: imageRUNNER ADVANCE 4000 series

Machine type Available Core functions	Monochrome Laser Multifunctional. (Reader/Printer separated) imageRUNNER ADVANCE 4025i: Print, Copy*, Scan*, Send* & Optional Fax imageRUNNER ADVANCE 4035i: Print, Copy*, Scan*, Send* & Optional Fax imageRUNNER ADVANCE 4045i: Print, Copy*, Scan*, Send* & Optional Fax imageRUNNER ADVANCE 4051i: Print, Copy*, Scan*, Send* & Optional Fax * Requires Duplex Color Image Reader Unit-E1
<b>PRINTER SPECIFICATIONS</b>	
Print speed	imageRUNNER ADVANCE 4025i: Up to 25 ppm (A4), Up to 15 ppm (A3), Up to 17 ppm (A4R), Up to 17 ppm (A5R) imageRUNNER ADVANCE 4035i: Up to 35 ppm (A4), Up to 22 ppm (A3), Up to 32 ppm (A4R), Up to 20 ppm (A5R) imageRUNNER ADVANCE 4045i: Up to 45 ppm (A4), Up to 22 ppm (A3), Up to 32 ppm (A4R), Up to 20 ppm (A5R) imageRUNNER ADVANCE 4051i: Up to 51 ppm (A4), Up to 25 ppm (A3), Up to 37 ppm (A4R), Up to 20 ppm (A5R)
Printing method	Monochrome laser beam printing
Print resolution	1200 dpi x 1200 dpi, 600 dpi x 600 dpi
Double sided printing	Automatic (Standard)
Printing from memory media	Supported memory media: USB memory key, Memory cards (SD, Compact Flash & Memory Stick via optional Multimedia Reader/Writer-A2). Supported file types for direct printing including printing from RemoteUI, Advanced Space and Web Access: JPEG, TIFF, PDF*, XPS* *Requires PS Printer Kit for PDF or Direct Print Kit for PDF/XPS. XPS direct print from removable media is not available.
Paper input (Standard)	2 x 550-sheet cassettes 80-sheet multi-purpose tray
Paper input (Option)	2 x 550-sheet cassettes (Cassette Pedestal) 1x 2700-sheet Side Paper Deck
Maximum paper input capacity	4980 sheets
Paper output capacity	Without Finisher: 250-sheets (80 gsm). With Inner Finisher: 1,000 sheets (with 1 tray), 100 + 500 sheets (with 2 trays) (80 gsm). With external Finisher: 3,000 (Lower tray: 1,700/Upper tray: 1,300 sheets) (80 gsm)
Finishing capabilities	Standard: Collate, Group. With optional Finishing units: Collate, Group, Offset, Staple, Booklet, Hole Punch
Supported media types	Cassette/s: Plain paper, Recycled paper, Colour paper, Heavy paper, Pre-punched paper Multi-purpose tray: Plain paper, Recycled paper, Colour paper, Heavy paper, Pre-punched paper, Bond, Transparency, Label
Supported media sizes	Paper Drawer 1, 2, 3 and 4: Standard size: A4, A4R, A3, A5, A5R, B5, Free size (139.7 mm x 182 mm to 297 mm to 431.8 mm) Multi-purpose tray: Standard size: A4, A4R, A3, A5, A5R, B5, Free size (99 mm x 148 mm to 297 mm to 432 mm)
Supported media weights	Cassette/s : 60 to 128 g/m <sup>2</sup> . Multi-purpose tray: 52 to 220 g/m <sup>2</sup> Duplex: 52 to 105 g/m <sup>2</sup>
Page Description Language(s)	UFRII (Standard). PCL5e/6 (Standard). Adobe PostScript Level 3 (Optional)
Fonts	PCL fonts : 93 Roman, 10 Bitmap font, 2 OCR font, Andalé Mono WT J/K/S/T* (Japanese, Korean, Simplified & Traditional Chinese) * requires optional PCL INTERNATIONAL FONT SET-A1 PS fonts : 136 Roman
Operating System compatibility	UFRII: Windows 2000 / XP / Server 2003 / Vista / Server 2008 / Windows 7 / Server 2008 R2, MAC OS X (10.4.9 or later) PCL: Windows 2000 / XP / Server 2003 / Vista / Server 2008 / Windows 7 / Server 2008 R2 PS: Windows 2000 / XP / Server 2003 / Vista / Server 2008 / Windows 7 / Server 2008 R2, MAC OS X (10.4.9 or later) PPD: MAC OS 9.1 or later, MAC OS X (10.2.8 or later) Windows 2000 / Server 2003 / Server 2008 / XP / Vista / 7 Please refer to <a href="http://software.canon-europe.com">http://software.canon-europe.com</a> for availability of print solutions for other Operating Systems and environments including AS/400, UNIX, Linux and Citrix. Some of these solutions are chargeable. SAP Device Types are available via the SAP Market Place
<b>COPY SPECIFICATIONS</b>	
Copy speed	imageRUNNER ADVANCE 4025i: Up to 25 cpm (A4), Up to 15 cpm (A3), Up to 17 cpm (A4R), Up to 17 cpm (A5R) imageRUNNER ADVANCE 4035i: Up to 35 cpm (A4), Up to 22 cpm (A3), Up to 32 cpm (A4R), Up to 20 cpm (A5R) imageRUNNER ADVANCE 4045i: Up to 45 cpm (A4), Up to 22 cpm (A3), Up to 32 cpm (A4R), Up to 20 cpm (A5R) imageRUNNER ADVANCE 4051i: Up to 51 cpm (A4), Up to 25 cpm (A3), Up to 37 cpm (A4R), Up to 20 cpm (A5R)
First Copy Output Time (FCOT)	imageRUNNER ADVANCE 4025i: Approx. 5.2 seconds or less imageRUNNER ADVANCE 4035i: Approx. 3.8 seconds or less imageRUNNER ADVANCE 4045i: Approx. 3.8 seconds or less imageRUNNER ADVANCE 4051i: Approx. 3.7 seconds or less
Copy resolution	Reading: 600 dpi x 600 dpi. Printing: 1200 dpi x 1200 dpi
Multiple copy	Up to 999 copies
Reduction / Enlargement	Zoom: 25-400% in 1% increments Fixed Zoom Ratio: 25%, 50%, 70%, 100%, 141%, 200%, 400%

<b>SCAN SPECIFICATIONS</b>	
Optional/Standard	Optional Colour Image Reader Unit-E1 provides: Colour Flatbed scan unit and 100-sheet Duplex Automatic Document Feeder (DADF)
Type	Colour Flatbed and Duplex Automatic Document Feeder (DADF)
Supported media size/s	A3, A4, A4R, A5, A5R, Custom sizes (W x L): Max 297 mm x 432 mm Min. 128 mm x 148 mm)
Supported media weight/s	Single-sided scanning: 42 to 128 g/m <sup>2</sup> Double-sided scanning: 50 to 128 g/m <sup>2</sup>
Scan resolution	100 dpi, 150 dpi, 200 x 100 dpi, 200 dpi, 300 dpi, 200 x 400 dpi*, 400 x 200dpi*, 400dpi*, 600dpi*. * Requires optional 512MB memory
Double sided scanning	2-sided to 2-sided (Automatic)
Scan speed	Single-sided (A4): 51 ipm 300dpi (Black & White), 51 ipm 300 dpi (Colour). Double-sided (A4): 17 ipm 300 dpi (Black & White), 17 ipm 300 dpi (Colour)
Scan methods	Push Scan: Send functionality available on all models. Pull Scan: TWAIN/WIA Pull scanning available on all models Scan to USB Memory Key: Available on all models
Pull scan specifications	TWAIN via Network TWAIN Driver (Colour Network ScanGear) Supported OS: Windows 2000 / Windows XP / Windows Server 2003 / Windows Vista / Windows Server 2008 / Windows 7 (32 bit, 64 bit in compatibility mode) WIA via Network WIA Driver. Supported OS: Windows Vista / Windows Server 2008 / Windows 7 (32 bit, 64 bit)
<b>SEND SPECIFICATIONS</b>	
Optional/Standard	Standard on all models (Requires Colour Image Reader Unit-E1)
Send resolution	100 dpi, 150 dpi, 200 x 100 dpi, 200 dpi, 300 dpi, 200 x 400 dpi*, 400 x 200 dpi*, 400 dpi*, 600 dpi*. * Requires optional 512MB memory
Destinations	E-Mail / Internet FAX (SMTP), PC (SMB, FTP), WebDAV, Google Docs with IR-ADV Cloud Connect MEAP application
Address Book / Speed dials	LDAP (1000) / Local (Max. 500)
File formats	TIFF, JPEG, PDF, XPS, High compression PDF/XPS, PDF/A-1b
Universal Send Feature Sets	Universal Send Advanced Feature Set-E1 (option): Outline PDF (Trace & Smooth), Searchable PDF/XPS, Reader Extensions PDF. Universal Send Security Feature Set-D1 (option): Encrypted PDF, Device Signature PDF/XPS. Universal Send Digital User Signature Kit-C1 (option): User Signature PDF/XPS
<b>FAX SPECIFICATIONS</b>	
Optional/Standard	Optional on all models
Modem speed	Super G3 33.6kbps (Up to 3 seconds/page <sup>1</sup> )
Fax resolution	Standard: 200 x 100 dpi. Fine: 200 x 200 dpi Super fine: 200 x 400 dpi. Ultra fine: 400 x 400 dpi
FAX memory	Up to 6,000 pages <sup>1</sup>
Speed dials	Max. 200
Group dials/destinations	Max. 199 dials
Sequential broadcast	Max. 256 address from the address book plus new 256 destinations
Memory backup	3 hour
Other features	Fax Forwarding, Dual Access, PC Fax (TX only)
<b>GENERAL SPECIFICATIONS</b>	
Warm-up Time	Approx. 38 seconds or less from power on
Interface type	USB 2.0 Hi-Speed, Ethernet: 1000BaseT/100Base-TX/10Base-T Wireless LAN (IEEE802.11b/g) (Optional) 1 x USB Host (2.0), Additional 2x USB Host (2.0) (Optional)
Network protocols	TCP/IP* (LPD / Port 9100 / WSD / IPP / IPPS / SMB / FTP), IPX/ SPX (NDS, Bindery), AppleTalk. *IPv4/IPv6 support
Processor Speed	1.2 GHz
Memory	1GB+256MB (Optional 512MB for colour scan and send above 300 dpi)
Hard Disk Drive	Standard 80GB Hard Disk Drive/ Optional 250GB Hard Disk Drive
Control panel	21.3 cm (8.4 inch) TFT SVGA Colour Touchscreen
Dimensions (W x D x H)	565 mm x 700 mm x 769 mm (without DADF) 565 mm x 700 mm x 909 mm (with DADF)
Installation space (W x D)	876 mm x 1150 mm (Main unit + Stack bypass + Cassette/s draws open)
Weight	Approx. 67.5 kg (without DADF), 75.4 kg (with DADF)
Operating environment	Temperature: 10 to 30°C (50 to 86°F) Humidity: 20 to 80% RH (no condensation)
Power Source	220-240 V (±10%), 50/60 Hz (±2 Hz), 4.3-5.6 Amp
Power Consumption	Maximum: Approx. 1.5 kW. Standby: Approx. 58 Watts (51 ppm), 60 Watts (45 ppm/35 ppm / 25 ppm). Energy Saver Mode: Approx. 28 Watts (51 ppm), 31W (45 ppm / 35 ppm / 25 ppm). Sleep mode: Approx. 1 W or less <sup>2</sup> Typical Electricity Consumption (TEC) rating <sup>3</sup> : 2.83 kwh / 2.52 kwh / 1.59 kwh / 1.07 kwh (51 ppm / 45 ppm / 35 ppm / 25 ppm)
Noise Levels	Sound Pressure <sup>4</sup> : Active: 53 dB / 52 dB / 51 dB / 50dB (51 ppm / 45 ppm / 35 ppm / 25ppm). Standby: inaudible

Software and printer management	iWMC - Centralised management of the device (Monitoring, configuration, address book, driver and resource management) eMaintenance compatibility via embedded RDS - enables Meter reading, Automatic consumables management and remote diagnostics CDS - Content Delivery System (Remote distribution of Firmware, iR Options and MEAP applications). Remote User Interface (RUI) Network ScanGear. NetSpot Device Installer MEAP (Multifunctional Embedded Application Platform). MEAP Web
Security Features	IP/ Mac Address Filtering, IPSEC, SNMP V3.0, IEEE 802.1X, Trusted Platform Module (TPM), Secure Print, Encrypted Secure Print, Hard Disk Drive Erase, Hard Disk Drive Mirroring & Encryption, Department ID, SSO, SSO-H, Mailbox, Encrypted PDF, User and Device signatures, Secure Watermarks, Document Scan locking, Hard Disk Drive removal, The following items require uniFLOW: My Print Anywhere secure print, Data Loss Prevention, Access Management for specific device features
<b>CONSUMABLES</b>	
Toner Cartridge/s	C-EXV 38 TONER (34200 pages <sup>5</sup> ) iR-ADV 4045i, iR-ADV 4051i C-EXV 39 TONER (30200 pages <sup>5</sup> ) iR-ADV 4025i, iR-ADV 4035i
<b>SPECIFICATIONS FOR OPTIONS</b>	
Staple Finisher	Name: Inner Finisher-D1 Number of Trays: 1 standard plus 1 optional Tray A Capacity: A4 / A5R: 100 sheets, A3 / A4R: 100 sheets Tray B Capacity: A4 / A5R: 1,000 sheets (without Tray A), 500 sheets (with Tray A), A3 / A4R 500 sheets, Paper Weight: 52 to 220 gsm Staple Position: Corner, Double Staple Capacity: A4: 50 sheets, A3 / A4R: 30 sheets Dimensions (W x D x H): 410 mm x 554 mm x 295 mm Weight: Approx. 12.5 kg  Name: Staple Finisher-G1 (External)* Number of Trays: 2 Tray A Capacity: A4 / A5R 1,300 sheets, A3 / A4R 650 sheets Tray B Capacity: A4 / A5R 1,700 sheets, A3 / A4R 650 sheets Paper Weight: 52 to 220 gsm Staple Position: Corner, Double Staple Capacity: A4: 50 sheets, A3 / A4R: 30 sheets Dimensions (W x D x H): 543 mm x 646 mm x 1097 mm Weight: Approx. 46 kg * Requires Buffer Pass Unit-H1
Booklet Finisher	Name: Booklet Finisher-G1 (External)* Number of Trays: 2 Tray A Capacity: A4 / A5R 1,300 sheets, A3 / A4R 650 sheets Tray B Capacity: A4 / A5R 1,700 sheets, A3 / A4R 650 sheets Paper Weight: 52 to 220 gsm Staple Position: Corner, Double, Booklet Stitch Staple Capacity: A4: 50 sheets, A3 / A4R: 30 sheets Booklet Stitch paper size: A3, A4R Booklet Stitch Staple Capacity: 16 sheets (64 pages, 64-81 gsm) x 10 jobs Dimensions (W x D x H): 648 mm x 646 mm x 1097 mm Weight: Approx. 75 kg * Requires Buffer Pass Unit-H1
Cassette Feeding units	Cassette Feeding Unit-AF1: Adds two additional front-loading, user-adjustable 550-sheet paper cassettes to the standard paper supply.
Paper Deck Unit	Name: Paper Deck Unit-B2 Paper Size: A4. Paper Weight: 60 to 128 gsm Paper Capacity: 2,700 sheets (80 gsm) Dimensions (W x D x H): 372 mm x 603 mm x 473 mm Weight: Approx. 37 kg
Puncher Unit/s	External 2 Hole Puncher-B2: 2 holes (Requires either the Booklet Finisher-G1 or Staple Finisher-G1) External 4 Hole Puncher-B2: 4 holes (Swedish) (Requires either the Booklet Finisher-G1 or Staple Finisher-G1) External 2/4 Hole Puncher-B2: 2 holes, 4 holes (French) (Requires either the Booklet Finisher-G1 or Staple Finisher-G1) Inner 2 Hole Puncher-A1: 2 holes (Requires Inner Finisher-D1) Inner 4 Hole Puncher-A1: 4 holes (Swedish) (Requires Inner Finisher-D1) Inner 2/4 Hole Puncher-A1: 2 holes, 4 holes (French) (Requires Inner Finisher-D1)
Document Insertion/ Folding Unit	Not Available
Document Insertion Unit	Not Available
Document Folding Unit	Not Available
<b>ADDITIONAL OPTIONS</b>	
	<b>COLOUR IMAGE READER UNIT-E1</b> (Duplex Automatic Document Feeder and Platen scanner) <b>STAMP INK CARTRIDGE-C1</b> <b>STAMP UNIT-B1</b> <b>ADF ACCESS HANDLE-A1</b> (Attaches to the document feeder, making access easier for seated users) <b>PRINTER COVER-E1</b> (Printer cover for main body without colour image reader unit) <b>INNER 2 WAY TRAY-H1</b> (Adds a second internal output tray and increases capacity to 450 sheets)

	<b>INNER FINISHER ADDITIONAL TRAY-A1</b> (Adds a second tray for the Inner Finisher-A1) <b>BUFFER PASS UNIT-H1</b> (Required for Staple Finisher G1 or Booklet Finisher G1) <b>STAPLE CARTRIDGE-D3 (R)</b> for Booklet Finisher-G1 <b>STAPLE CARTRIDGE-J1 GP</b> for Inner Finisher-D1 <b>UTILITY TRAY-A2</b> (Additional tray to hold an external USB keyboard.) <b>imageRUNNER ADVANCE C2000 Plain Pedestal</b> (Alternative to cassette pedestal without paper capacity) <b>COPY CARD READER-F1</b> (Magnetic physical card access system) <b>COPY CARD READER ATTACHMENT-B2</b> (Attachment kit for Copy Card Reader) <b>C-EXV38/39 DRUM UNIT</b> <b>SUPER G3 FAX BOARD-AK1</b> (Adds fax functionality) <b>FAX BOARD (2 LINE)-AK1</b> (Adds second fax line) <b>DIRECT PRINT KIT (PDF/XPS)-H1</b> (Enables users to print PDF/XPS files directly to the device) <b>BARCODE PRINT KIT-D1</b> (Enables barcode printing via jet caps technology) <b>VOICE GUIDANCE-F2</b> (Recorded voice provides confirmation of basic copy menu settings, making the system easier to use for the visually impaired.) <b>VOICE OPERATION-C2</b> (Enables the user to set various functions on the device using verbal instructions and audible feedback.) <b>PS PRINTER KIT-AN1</b> (Adds Genuine Adobe PostScript Support. Also enables users to print PDF/PS/EPS files directly to the device) <b>DATA ERASE-C1</b> (Overwrites all temporary job data after completion and overwrites permanent data (i.e. mailbox files) as soon as it is deleted, preventing unauthorised access.) <b>HDD DATA ENCRYPTION &amp; MIRRORING KIT-C4</b> (Hard disk drive accessory pack, providing encryption and mirroring of both temporary and permanent data. Encryption enables copied or scanned images to be encrypted BEFORE they are saved on the device's hard drive. The pack includes the Common Criteria level EAL3 certified Canon MFP security kit 2.00. Mirroring copies all data in real time, providing a highly reliable back-up.) <b>ENCRYPTED PRINTING SOFTWARE-D1</b> (Encrypts the print job in transit to the device and requires a password at the printer before sensitive documents are printed.) <b>SECURE WATERMARK-B1</b> (Deters duplication of sensitive printouts by embedding hidden watermarks that become visible when copied.) <b>DOCUMENT SCAN LOCK KIT-B1</b> (Offers embedded security to prevent copying of sensitive printed documents whilst providing the ability to analyse any security breach of the document.) <b>WEB ACCESS SOFTWARE-H1</b> (Provide access to websites and other web-based online content) <b>USB DEVICE PORT-D1</b> (Adds two additional USB Ports to use with uniFLOW or 3rd party card readers or the Multimedia Reader/Writer-A2 for additional media support.) <b>WIRELESS LAN BOARD-B2</b> (Wireless connectivity for the device) <b>ADDITIONAL MEMORY TYPE A</b> (512MB)(Required for 600dpi colour scan & send.) <b>2.5INCH/80GB HDD-C1</b> (Additional HDD for mirroring function.) <b>2.5INCH/250GB HDD-D1</b> (A replacement HDD to increase the storage space on the device. Note: Mirroring function requires second 250GB HDD) <b>REMOVABLE HARD DISK KIT-AF1</b> (Enables customers to lock the hard disk(s) into the device for normal operation and to remove them to a secure location after powering down.) <b>EXPANSION BUS-F2</b> (Required to install the Wireless LAN Board-B2.) <b>REMOTE FAX-A1</b> (Enables the device to send and receive fax from another device connected with a fax board.) <b>MULTIMEDIA READER/WRIER-A2</b> (External multi-slot card reader/writer.) <b>SERIAL INTERFACE KIT-K1</b> (Serial interface for Cost Recovery Solutions.) <b>COPY CONTROL INTERFACE KIT-A1</b> (CC6 interface conversion into RS232 interface.) <b>PCL INTERNATIONAL FONT SET-A1</b> (Adds PCL support for Andalé Mono WT J/K/S/T(Japanese/ Korean/ Simplified Chinese/ Traditional Chinese)) <b>REMOTE OPERATORS SOFTWARE KIT-B1</b> (Allows use of device control panel screens from remote computers.) <b>ACCESS MANAGEMENT SYSTEM Kit-B1</b> (Requires uniFLOW software solution. The AMS kit enables uniFLOW to restrict access to specific functions on a device by user.) <b>FL CASSETTE-AQ1</b> (Spare 550 sheet cassette tray for cassette 1) <b>FL CASSETTE-AM1</b> (Spare 550 sheet cassette tray for cassette 2, 3 and 4)
	<b>Standard disclaimers</b> Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.™ and ©: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries. <b>Footnotes</b> 1. Based on ITU-T Standard Chart No. 1 2. Typical Electricity Consumption (TEC) rating represents the typical electricity consumed by a product during 1 week, measured in kilowatt-hours (kWh). The test methodology is defined by ENERGY STAR ( <a href="http://www.eu-energystar.org">http://www.eu-energystar.org</a> ). 3. 1 watt sleep mode may not be possible in all circumstances. Certain network configurations and options may prevent the device from entering deep sleep mode. Please refer to the user guide for more information 4. Declared noise emission in accordance with ISO 7779 5. Based on 6% coverage



 **ImageRUNNER**  
ADVANCE

 **uniFLOW**

**IW**  
Desktop

 **eMaintenance**

**Therefore**  
PEOPLE PROCESS INFORMATION

 **Common Criteria**

 **ENERGY STAR**

 **Adobe PostScript 3™**

 **eCopy**

**USB Print & Scan**

Canon Inc.  
canon.com

Canon Europe  
canon-europe.com

English Edition 0163W620  
01/12/v1  
© Canon Europa N.V., 2012

Canon (UK) Ltd  
Woodhatch  
Reigate  
Surrey  
RH2 8BF  
Tel.: 01737 220000  
Fax: 01737 220022  
canon.co.uk

Canon Ireland  
3006 Lake Drive  
Citywest, Saggart  
Co. Dublin, Ireland  
Tel.: 01 2052400  
Fax: 01 2052525  
canon.ie

**Canon**