

Add a professional touch with this compact and efficient network-ready 4-in-1

i-SENSYS
MF4580dn

you can



The compact, network-ready 4-in-1 mono laser with double-sided ADF. Boost productivity in any small office with this compact, network-ready 4-in-1 mono laser multifunctional. Offering double-sided capabilities, this stylish device is energy efficient and easy to use.

25 PPM 9 SECONDS FIRST PRINT OUT TIME
NETWORK-READY MONO LASER 4-IN-1
AUTOMATIC DOUBLE-SIDED PRINTING
STYLISH, COMPACT DESIGN
EASY TO USE INTUITIVE LCD DISPLAY
EASY NETWORK SCAN FUNCTION
50-SHEET DOUBLE-SIDED AUTOMATIC DOCUMENT FEEDER
ENERGY EFFICIENT

Key features

- Combine network print, copy, scan & fax in one to save time and money
- Productive black and white laser print speeds of 25 ppm
- Stylish, minimal, space-saving design with automatic double-sided printing
- Intuitive LCD display for a better user experience
- 50-sheet Double-sided Automatic Document Feeder for double-sided copy and scan
- Up to 1200 x 600 dpi resolution for high quality prints and copies
- Fast First Copy Out Time of 9 seconds or less
- Easy to use network colour scanning function
- Convenient, easy to use All-in-One cartridge
- Class leading energy efficiency

What's in the Box

Main unit, Cartridge 728 starter, power cord, telephone line cable, starter guide and warranty card - with user software and manual CDs.

Dimensions (WxDxH)

390mm x 429mm x 361mm

Supported OS

Windows 7/Server 2008/
Server 2003/2000/ XP/ Vista
Mac OS X Version 10.4.9 - 10.6.x
(Web distribution only)
Linux (Web distribution only)



PRINT



COPY



FAX



SCAN

Canon

Specifications



- 1 Flatbed and DADF
- 2 250-sheet tray
- 3 Cartridge 728

PRINTER Print speed Printing method Print quality Print resolution First Print Out Time Double sided printing Printer languages Print margins Toner saver mode	Up to 25 ppm (A4) Monochrome laser beam printing Up to 1200 x 600 dpi with Automatic Image Refinement 600 x 600 dpi 6 secs Automatic UFRIL-LT 5 mm-top and bottom, 5 mm-left and right Yes
COPIER Copy speed First Copy Output Time (FCOT) Copy resolution Copy modes Double sided copying Multiple copy Reduction / Enlargement Toner saver mode Other features	Up to 25 ppm (A4) Approx. 9 seconds or less Up to 600 x 600 dpi Text, Text/Photo, Text/Photo+, Photo 2-sided to 2-sided (Automatic) Up to 99 copies 25-400% in 1% increments Yes Memory sort, 2 on 1, 4 on 1, ID Card Copy
SCANNER Type Scan resolution Colour scanning depth Greyscales Compatibility Max. scan width	Colour Optical: Up to 600 x 600 dpi Enhanced: Up to 9600 x 9600 dpi 24 bit/24 bit (input/output) 256 levels TWAIN, WIA 216 mm
FAX Modem speed Receive mode Fax resolution FAX memory Speed dials Group dials/destinations Sequential broadcast Memory backup Double sided faxing Other features	Super G3 33.6kbps FAX Only, Manual, Answering, Fax / Tel Auto SW Standard: 200 x 100 dpi Fine: 200 x 200 dpi Photo: 200 x 200 dpi Super fine: 200 x 400 dpi Up to 256 pages ¹ Max. 104 (including 4 one-touch dials) Max. 50 destinations Max. 114 locations 5 mins Yes (Reception/transmit) Dual Access, Remote RX, PC Fax (sending only)

MEDIA HANDLING Scanner type Paper input (Standard) Paper output Media types Media sizes	Flatbed and Duplex Automatic Document Feeder (DADF) 250-sheet tray 1-sheet manual feed slot 50-sheet DADF 100-sheet Plain paper, Heavy paper, Rough paper, Recycled paper, Colour paper, Transparency, Label, Envelope, Index Card Tray: A4, B5, A5, Executive, Envelope (COM10, DL, B5, C5), LTR, LGL, Statement, Custom sizes: Width 76 x 216 mm; Length 210 x 356 mm. Manual feed slot: A4, B5, A5, Executive, Envelope (COM10, Monarch, DL, B5, C5), Index card, LTR, LGL, Statement, Custom sizes: Width 76 x 216 mm; Length 127 x 356 mm. DADF: A4, B5, A5, Legal, Letter, Custom (W x L): Max 216 x 356 mm Min 105 x 148 mm. Tray: 60 to 163 g/m ² Manual feed slot: 60 to 163 g/m ²
INTERFACE & SOFTWARE Interface type Operating System compatibility Software and printer management	USB 2.0 Hi-speed, 10BASE-T/100BASE-TX Windows 7/Server 2008/Server 2003/2000/ XP/ Vista Mac OS X Version ² 10.4.9 - 10.6.x ³ Linux ^{3,4} Presto! Page Manager, MF Toolbox, Remote User Interface (RUI)
GENERAL FEATURES Duty cycle Warm-up Time Memory Control panel Dimensions with trays (W x D x H) Installation space (W x D x H) Weight Operating environment Power Source Power Consumption Noise Levels	Max. 10,000 pages per month Approx. 12 seconds from power on 64 MB 5 lines BW LCD 390 mm x 429 mm x 361 mm 431 mm x 604 mm x 663 mm Approx 13.4 Kg Temperature: 10 to 30°C (50 to 86°F) Humidity: 20 to 80% RH (no condensation) 220-240 V (±10%), 50/60 Hz (±2 Hz) Maximum: Approx. less than 1220 W Active: Approx. less than 500 W Sleep mode: Approx. 3 W Typical Electricity Consumption (TEC): 1.00 kWh/week Sound Pressure Active: 43 dB(A) or less Standby: Inaudible
CONSUMABLES Cartridges	Cartridge 728 (2,100 pages ⁵)
ACCESSORIES/OPTIONS	TELEPHONE KIT 6
Standard disclaimer All specifications subject to change without notice Footnotes 1 Based on ITU-T Standard Chart No. 1 2 Mac OS support Scan function via USB only 3 Web distribution only 4 Linux support printing only. Driver release January 2011 5 Ships with 1,000 pages starter cartridge 6 Based on ISO/IEC 19752	

